

PROTECTIT PHOS RUST REMOVER



OVERVIEW

PHOS Rust Remover is a 2-part acid/base system for the refurbishment of oxidised substrates. Use in conjunction with Deep Cleaner alkaline neutraliser.

PHOS Rust Remover is ideally suited for the heavy duty cleaning/refurbishment of tiled, porcelain and natural stoneware.

PHOS Rust Remover is designed to clean and degrease the most oxidised surfaces.

PHOS Rust Remover is an acid etching.

BENEFITS

PHOS A is a powerful alternative to shot blasting and erosive polishing techniques. It is Fast-acting, with powerful degreasing properties and has a non-flammable, non-caustic effect on building materials.

APPLICATION

This product is specially designed for the refurbishment and to degrease and clean all synthetic and stone surfaces. Shake the container well before use

PHOS RUST REMOVER (R13)

Use a low pressure sprayer to apply and then leave it to soak, allowing 5-15 minutes to work.

DEEP CLEANER (R26)

Use a low pressure sprayer to apply and then leave it to soak, allowing 5-10 minutes for the product to neutralise and clean the surface.

Gentle agitation can be performed with a stiff brush prior to rinsing.

Guidelines for use:

Apply product/s to the surface moving from bottom to top. Rinse fully with water following application of both parts of the system. The surface is ready to be treated or painted as soon as it has dried.

To prevent future soiling, it is recommended to use a suitable protective treatment.

PRODUCT CHARACTERISTICS (PHOS RUST REMOVER)

Colour	Clear
Odour	Characteristic Odour
Form	Liquid
Coverage	4-8 m ² per litre
PH	1
Application Temperatures	Minimum +5°C Maximum 30°C
Shelf Life	24 months from the date of manufacture in the original unopened container

PRODUCT CHARACTERISTICS (DEEP CLEANER)

Colour	Pale Yellow
Odour	Characteristic Odour
Form	Liquid
Coverage	4-8 m ² per litre
PH	13
Application Temperatures	Minimum +5°C Maximum 30°C
Shelf Life	24 months from the date of manufacture in the original unopened container

SURFACE PREPERATION

Ensure adequate ventilation at all times and wear protective clothing, gloves and safety goggles.

Apply with a brush, long pile roller

Be careful to mask off/protect all surfaces not intended to be treated.

PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)

CLEANING OF EQUIPMENT

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

IMPORTANT / LIMITATIONS

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption. Keep out of reach of children. Keep in a dry place between 5°C and 30°C in the original container.

BEFORE



AFTER

